



VHF MARINE TRANSCEIVER

IC-M422



Optional COMMANDMICII™, HM-157B

FORCE 5 AUDIO™

Submersible
1m depth for 30 minutes

Fully featured compact marine VHF

- Built-in DSC That Meets RTCM SC-101
- Individual, Group & All Ships Call
- Position Request & Position Report with a Third Party GPS Receiver
- Submersible Construction, Including Microphone (1m depth for 30 minutes*)

* Equivalent to IPX7 of the international standard IEC 60529 (2001).

- Public Address and RX Speaker Functions
- Simple Operation with Large Buttons
- Simple Tag Scanning Function
- Optional COMMANDMICII™ Provides 2nd Station Capability
- Loud Speaker Audio

Icom Inc.

Built-in DSC meets RTCM SC-101

Built-in DSC watch function monitors Ch 70 (DSC channel) activity, even while you are receiving another channel. In an emergency situation, a formatted distress call can be sent at the touch of a button.

Digital Selective Calling Features

DSC uses a unique ID (MMSI code) similar to a telephone number, allowing you to make contact with a specific boater or group of boaters in your area. A total of 100 address IDs can be stored with a 5-character name.

Position Request and Position Report with External GPS Receiver

With an external GPS receiver, the position request and position report functions allow you to exchange ships position. The received position information can be plotted on a third party GPS or other navigation equipment

which accepts NMEA data format. The polling (request/reply) function checks whether a specific ship is in the communication range.

New public address (PA) and RX speaker functions

Use the hand microphone as part of a public address system and make an announcement on-board or to shore through an external loud speaker or hailer. The RX speaker function allows you to monitor the received audio from the loud speaker or hailer while you are on the deck or tower.

New optional COMMANDMICII™

The new optional COMMANDMICII™ makes it convenient for using the IC-M422 from a separate cabin or tower. It allows you to control most functions* of the IC-M422, including remote power ON/OFF, PA and RX speaker functions. (*except DSC operation)

Force 5 Audio

The front facing speaker offers loud, crisp reception that is easy to hear, even over engine or wind noise.

Local function

The local function turns ON the attenuator and gives you the option to reduce interference from strong stations.

And More

- Submersible* (1m depth for 30 minutes.) Equivalent to IPX7, except cables.
- Large 2-digit channel with scrolling names
- 7-step keypad backlighting
- 4-step LCD contrast
- Dualwatch and Tri-watch functions
- Super white and black versions available.
- Simple and easy tag scanning system
- NOAA weather channels with alert function
- Low voltage indicator for low battery alert

SPECIFICATIONS

GENERAL	
• Frequency range	: Tx 156.025–157.425MHz Rx 156.050–163.275MHz
• Usable channels	: USA, CAN, INT, WX channels
• Type of emission	: 16K0G3E (FM), 16K0G2B (DSC)
• Power supply requirement	: 13.8V DC ±15%
• Current drain	: Tx 5.5A (at 25W output) Rx 1.5A (at AF max.) (at 13.8V DC)
• Operating temp. range	: -20°C to +60°C; -4°F to +140°F
• Antenna impedance	: 50Ω (SO-239)
• Dimensions (W×H×D)	: 164×78×139.3mm; (projections not included) 6 ¹ / ₂ ×3 ¹ / ₁₆ ×5 ¹ / ₃₂ in.
• Weight (approx.)	: 1070g; 2.4lb
• NMEA In/out formats	: RMC, GGA, GNS, GLL

TRANSMITTER	
• Output power	: 25W, 1W (at 13.8V DC)
• Modulation system	: Variable reactance freq. mod.
• Max. freq. deviation	: ±5.0kHz
• Frequency error	: ±10ppm (-20°C to +60°C)
• Spurious emissions	: Less than -70dBc
• Residual modulation	: More than 40dB
• Adjacent Ch. power	: More than 70dB
• Audio frequency response	: +1dB to -3dB of 6dB octave from 300Hz to 2500Hz

RECEIVER	
• Intermediate freq.	: 1st 21.7MHz, 2nd 450kHz
• Sensitivity	: 0.22μV typical at 12dB SINAD
• Squelch sensitivity	: Less than 0.22μV
• Adjacent Ch. selectivity	: More than 70dB
• Spurious response	: More than 70dB
• Intermodulation	: More than 70dB
• Hum and noise	: More than 40dB
• Audio output power	: 4.5W typical at 10% distortion with a 4Ω load
• Audio frequency response	: +1dB to -3dB of -6dB octave from 300Hz to 3000Hz

Supplied accessories:
 • Hand microphone, HM-150B/SW
 • DC power cable
 • Mounting bracket kit

All stated specifications are subject to change without notice or obligation.

OPTIONS

HM-157B/SW REMOTE-CONTROL MICROPHONE

Up to 21.3m (70ft) of freedom from the IC-M422 with two OPC-999 extension cables. Allows you to control most functions of the IC-M422 including remote power ON/OFF, PA and PX speaker functions (except DSC operation).

Size (W×H×D): 63.5×125.0×31.4mm; 2¹/₂×4²⁹/₃₂×1¹/₄ in.
 Weight (approx.; with 3m curl cable): 250g; 8.8oz

Supplied accessories :

- 6.1m (20ft) of cable
- Microphone hanger
- Mounting base for cable connector

COMMANDMICII and FORCE5AUDIO logo are trademarks of Icom Inc. (Japan) in the United States.

OPC-999 EXTENSION CABLE FOR HM-157B/SW

6.1m (20ft) of extension cable for additional lengthening for use with COMMANDMICII™. Up to two cables available.

HM-150B/SW HAND MICROPHONE

Super white and black are available. Same as supplied.

MB-69 FLUSH MOUNT KIT

For flush-mounting the IC-M422 to a flat surface.



Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE,
 Bellevue, WA 98004, U.S.A.
 Phone : +1 (425) 454-8155
 Fax : +1 (425) 454-1509
 E-mail : sales@icomamerica.com
 URL : <http://www.icomamerica.com>

Icom Canada

Greenwood Centre #150-6165 Highway 17,
 Delta, B.C., V4K 5B8, Canada
 Phone : +1 (604) 952-4266
 Fax : +1 (604) 952-0900
 E-mail : info@icomcanada.com
 URL : <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

A.B.N. 88 006 092 575
 Unit 1 / 103 Garden Road,
 Clayton VIC 3168 Australia
 Phone : +61 (03) 9549 7500
 Fax : +61 (03) 9549 7505
 E-mail : sales@icom.net.au
 URL : <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki,
 Auckland, New Zealand
 Phone : +64 (09) 274 4062
 Fax : +64 (09) 274 4708
 E-mail : inquiries@icom.co.nz
 URL : <http://www.icom.co.nz>

Icom (Europe) GmbH

Communication Equipment
 Himmelgeister Str. 100,
 D-40225 Düsseldorf, Germany
 Phone : +49 (0211) 346047
 Fax : +49 (0211) 333639
 E-mail : info@icom-europe.com
 URL : <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. de Gracia a Manresa Km. 14,750
 08190 Sant Cugat del Valles Barcelona, Spain
 Phone : +34 (93) 580 26 70
 Fax : +34 (93) 580 04 46
 E-mail : icom@icomspain.com
 URL : <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay,
 Kent, CT6 8LD, U.K.
 Phone : +44 (01227) 741741
 Fax : +44 (01227) 741742
 E-mail : info@icomuk.co.uk
 URL : <http://www.icomuk.co.uk>

Icom France Sa

Zac de la Plaine, 1,
 Rue Brindejonc des Moulinais BP 5804,
 31505 Toulouse Cedex, France
 Phone : +33 (5) 61 36 03 03
 Fax : +33 (5) 61 36 03 00
 E-mail : icom@icom-france.com
 URL : <http://www.icom-france.com>

Icom Polska


Spot, 3 maja 54, Poland
 Phone : +48 (58) 550 7135
 Fax : +48 (58) 551 0484
 E-mail : icompolska@icompolska.com.pl
 URL : <http://www.icompolska.com.pl>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
 Taipei, Taiwan, R.O.C.
 Phone : +886 (02) 2559 1899
 Fax : +886 (02) 2559 1874
 E-mail : sales@asia-icom.com
 URL : <http://www.asia-icom.com>

Beijing Icom Ltd.

10C07, Long Silver Mansion, No.88, Yong Ding
 Road, Haidian District, Beijing, 100039, China
 Phone : +86 (010) 5889 5391/5392/5393
 Fax : +86 (010) 5889 5395
 E-mail : bjicom@bjicom.com
 URL : <http://www.bjicom.com>



Icom Inc. (Japan), is an ISO 9001 and ISO 14001 certification acquired company.

Your local distributor/dealer: